



urbanspec CL Semi Enclosed Bike Shelters

Providing reliable, cost-effective weather protection for a single row of cycles, the standard urbanspec CL Semi-enclosed Bike Shelter utilises an asymmetric quadrant roof and is manufactured as a single 4100mm module, providing cover for up to 10 cycles with Sheffield-type stands. Custom dimensions can be specified, with additional modules able to be joined in-line or as a compound.

urbanspec CL Semi-Enclosed Bike Shelters are supplied with height-adjustable steel base plates that can be fixed to foundation pads either below or flush with the finished surface, depending on site and finish requirements. Surface fixed Sheffield toast rack cycle stands are supplied as standard with root-fix specification available.

Depending on project requirements, urbanspec CL Semi-Enclosed Cycle Shelters are supplied with height-adjustable steel base plates. These can

be fixed with foundation pads that lie either below or finished with the finish surface. Sheffield toast rack cycle stands are supplied surface fixed as standard, with specifications for root fixing also available.

The clear view solid polycarbonate cladding is manufactured with UV protection on both sides providing excellent weathering properties and resistance from vandalism. The polycarbonate roof panels can also be specified to cover the central aisle, helping to increase weather protection.

urbanspec CL Semi-Enclosed Cycle Shelters are supplied with HD galvanised coating as standard, while colour powder coat options can be specified to include coordinated cycle stands. Shelters can also be specified as a secure compound with the addition of steel mesh sliding gates and a range of access control systems.

Secure Compound

Shelters can also be specified as a secure compound with the addition of steel mesh sliding gates and a range of access control systems

Customise

HD galvanised coating is standard; colour powder coat options can be specified to include coordinated cycle stands

Cladding

The clear view solid polycarbonate cladding is manufactured with UV protection on both sides providing excellent weathering properties and resistance from vandalism



Product Capacity & Dimensions

CL



Model	Hoop Storage	Depth (mm)	Width (mm)	Height (mm)
CL4	4x Cycles	3000	1790	2010
CL6	6x Cycles	3000	2630	2010
CL8	8x Cycles	3000	3430	2010
CL10	10x Cycles	3000	4270	2010
CL12	12x Cycles	3000	5070	2010
CL16	16x Cycles	3000	6710	2010
CL 20	20x Cycles	3000	8350	2010

CLE



Model	Hoop Storage	Depth (mm)	Width (mm)	Height (mm)
CLE 16	16x Cycles	5240	3430	2260
CLE 20	20x Cycles	5240	4240	2260
CLE 24	24x Cycles	5240	5060	2260

urbanspec CL is manufactured in 10 cycle capacity. Custom dimensions are available to special order.

Locking Systems



Latch + Battery Code Lock



Latch + Eurocylinder Lock



Latch + RFID Lock



Slide Bolt + Padlock



Latch + Eurocylinder Lock Sliding Door

Cladding & Finish Examples



Hot-Dip Galvanised

Firenze Colour Powder Coat

Cycle Rack Options



Rail Fix (Toast Rack)



Baseplate



Root Fix

