



## urbanspec CLS Double row Symmetric Bike Shelters

The larger version of the CS bike shelter, urbanspec CLS provides weather protection for two rows of bike stands with a 4000mm cover width. With the same architectural design from a symmetric barrel-vaulted roof and centrally supported structure.

Configurable for layout to optimise bike storage capacity, CLS can be specified as a series unit with add-on bays or combined with CS Shelters to form a bike shelter compound where the site is secure or within an area of high pedestrian traffic and the overall visual impact of the structure is a consideration.

urbanspec CLS provides 4000mm cover width for a double row of bike racks cycles with standard 'sheffield' type stands, while the CLST model accommodates two-tier cycle racks for high storage capacity applications. Custom dimensions can be accommodated as a special build. The radius steel support structure has a central base plate design that can be specified

for either surface fix or subsurface ground fixings

urbanspec bike shelters are UK manufactured and the all-steel framework has a hot dip galvanised finish as standard. Customisation options include colour powder coated frames and racks, bespoke laser cut logo to end frames and LED lighting.

UV protected polycarbonate roof panels with aluminium glazing system combine clean aesthetics with a long service life. The radius steel support structure has a central base plate design enabling either surface fix or subsurface ground fixings to be accommodated.

All bike shelter models are available for download as CAD blocks with NBS Specification References.

**Secure Compound**  
CLS can be specified as a series unit with add-on bays or combined with CS Shelters to form a bike shelter compound


**Customise**  
Options include colour powder coated frames and racks, custom laser cut logo to end frames and LED Lighting



**Roof Panels**  
UV protected polycarbonate roof panels with aluminium glazing system combine clean aesthetics with a long service life.


## Product Capacity & Dimensions

### CLS



Model	Hoop Storage	Depth (mm)	Width (mm)	Height (mm)
CLS 20	20x Cycles	4050	5150	3060
CLS 24	24x Cycles	4050	6150	3060

### CLST



Model	Two-Tier	Depth (mm)	Width (mm)	Height (mm)
CLST 40	40x Cycles	4050	5150	3260
CLST 52	52x Cycles	4050	6150	3260

urbanspec CLS is manufactured in 3 standard model types; 20 and 24 cycle capacities and 52 cycles with the two-tier cycle rack system. Custom dimensions are available to special order.

## Cladding & Finish Examples



Hot-Dip Galvanised

Firenze Colour Powder Coat

## Cycle Rack Options



Rail Fix (Toast Rack)



Baseplate



Root Fix



Two-Tier

